

LARGE AND OFF-ROAD SUV'S COMPATIBLE WITH TRACKNGO						
Marque	Model	Low range (4L)	tire size	outside dia.	available in	rear differential lock
Cadillac	Escalade **	opt.	275/65r18	32.1	North America	opt.
Chevrolet	Suburban**	opt.	265/65R18	31.6	North America	opt.
Chevrolet	Tahoe**	opt.	265/65R18	31.6	North America	opt.
Dodge	Durango**	opt.	265/60R18	31.2	North America	opt.
Ford	Expedition**	opt.	265/65R18	31.6	North America	opt.
GMC	Yukon**	opt.	275/55R20	31.9	North America	opt.
Hummer	H2 - H3	std	265/75R16	31.6	world	std
Jeep	Grand Cherokee	std	265/50R20	30.6	world	std
Jeep	Wrangler (all types)	std	255/75R17	32	world	std
Land Rover	Defender 130	std	235/85R16	31.7	Europe	std
Land Rover	Defender 90	std	265/75R16	31.6	Europe	std
Land Rover	Defender 110	std	265/75R16	31.6	Europe	std
Land Rover	Range Rover	std	255/55R20	30.7	world	std
Lexus	LX570	std	285/60R18	31.5	world	std
Lincoln	Navigator**	opt.	265/70R18	32.4	North America	opt.
Mercedes	GL Class	std	275/55R19	30.9	Europe	std
Mitsubishi	Pajero	std	265/65R17	30.6	Europe	std
Nissan	PathFinder **	opt.	255/65R17	30.2	world	opt.
Nissan	Xterra (PRO-4X)	std	265/75R16	31.6	world	std
Nissan	Patrol	std	275/65R17	31.1	Europe	std
Nissan	Armada**	opt.	265/70R18	32.4	North America	opt.
Toyota	F.J. Cruiser**	opt.	265/70R17	31.6	world	opt.
Toyota	LandCruiser 100	std	285/65R17	31.6	Europe	std
Toyota	LandCruiser 200	std	285/65R17	31.6	Europe	std. Split-diff.
Toyota	LandCruiser Prado	std	265/65R17	30.6	Europe	std
Toyota	Sequoia**	opt.	275/65r18	32.1	North America	opt.
UAZ	Patriot*, Pickup*, Hunter*	std	235/70R16	29	Russia	unknown
*:original tires must be increase to a minimum outside diameter of 31 inches(780 mm)						
**: low range (4L) is optional on these vehicles. <u>Your vehicle must have "4L" option.</u>						